

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Issued by DBI Certification, notified body No. 2531.

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

MH075 - Fire resisting doorset

Scope: Safety and performance requirements applicable to fire and/or smoke control products limited to;
Industrial, commercial and garage doors and gates according to the scope covered by EN 13241 or
Windows (including roof windows) and external pedestrian doorsets covered by EN 14351-1.

The product fulfils the essential characteristic of: See Annex 1

Intended use: Fire and/or smoke compartmentation and/or escape routes

Placed on the market under the name or trade mark of:
Door System A/S
Agerskovvej 16
8362 Hørning
Denmark

and produced in the manufacturing plant:
CPA40009

This attests that all provisions concerning the performance described in Annex ZA of the standard(s)

EN 16034:2014 : **Pedestrian doorsets, industrial, commercial, garage doors and openable windows - Product standard, performance characteristics - Fire resisting and/or smoke control characteristics**

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

CONSTANCY OF PERFORMANCE OF THE CONSTRUCTION PRODUCT.

This certificate was first issued on 2019-11-19 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The attached annexes form part of this certificate.

Date of issue: **2025-02-12**.

(This certificate supersedes the previous version of this certificate issued 2022-11-04)



Merete Poulsen
Responsible for evaluation



Allan Christensen
Responsible for certification decision

The certificate shall be reproduced in extensor
– extracts only with written permission from DBI Certification A/S.

Annex 1:

Product description: MH075-Fire sesisting doorset			
Essential Characteristics	Subclauses in this and other European Standard(s) related to essential characterisrtics	Performance	Remarks
Resistance to fire	4.1 (classification)	El ₂ 60 single leaf doorset	The classification is valid for fire resistance from either side
Smoke control	4.2 (classification)	NPD	
Ability to release	4.3 (description, test report)	NPD	
Self-closing	4.4 (classification)	C	Dependent on the use of door hardware, the door may be classified with or without the self-closing classification C.
Durability of ability to release	4.5.1 (description, test report)	NPD	
Durability of self-closing	4.5.2.1 (classification) 4.5.2.2 (description, test report)	NPD	
	<ul style="list-style-type: none"> Against degradation (cycling testing) Against ageing (corrosion) 		

	Report no.	Date	Accredited Lab.
Classification report:	PCA10434A Rev. 05	2024-11-01	DBI reg. no.: 0012
Exap report:	PHB10029A. Rev. 05	2024-11-01	DBI reg. no.: 0012
Test report:	PGA10783A	2016-04-14	DBI reg. no.: 0012
	PGA10843A	2016-04-14	DBI reg. no.: 0012
	PGA10862A	2016-08-05	DBI reg. no.: 0012
	PGA10630 Rev. 1	2017-02-14	DBI reg. no.: 0012
	PGA10752A Rev. 2	2017-02-14	DBI reg. no.: 0012
	PGA11908A. Rev. 01	2021-11-11	DBI reg. no.: 0012
	PGA12099A, Rev. 00	2022-0916	DBI reg. no.: 0012
	PGA12099B. Rev. 00	2022-09-16	DBI reg. no.: 0012
	PGA12099C. rev. 00	2022-10-10	DBI reg. no.: 0012

Technical documentation:

Field of Application including Build Standard is described in details in DBI report no. PCA10434A Rev. 05, 2024-11-01.

The certificate shall be reproduced in extensor
 – extracts only with written permission from DBI Certification A/S.